

CAN-8 I CAN module, 8 Inputs

Compact Input Module with Popular Deutsch DT Connector



FEATURES

CAN Control

Send CAN messages from up to 8 analog or digital inputs

Rugged and Compact

Compact module mounts in tight locations.

Easy Installation

Deutsch connector for simple, clean installation.

Customizable

Compatible with popular CAN systems

OPERATION

CAN control

Up to 8 inputs transmitted as CAN messages. Consult factory for CAN message details and point-map.

Outputs

Up to 8 analog or digital inputs.

ORDERING INFORMATION

PART#	DESCRIPTION
CAN-8I	CAN input module

SPECIFICATIONS

General	Power Requirement	10-24vdc, 100mA nominal + power to loads
	Fuses	Customer-supplied fuse should be installed in field wiring
	CAN Interface	Compatible with most popular CAN controllers, consult factory
	Inputs	Up to 8 analog or digital 0-10vdc
	Field Wiring	Deutsch DT06-12S plug and contact kit
		Crimp contacts provided for 16-18awg stranded wire
Enclosure		ABS, Potted box, NEMA 4X
		Approximate size: 5.5"L x 3.6"W x 2"H
Environmental	Storage	-40°C to 85°C
	Operating	-10°C to 60°C

PAGE 57 MIRATRON 866-417-5008 503-352-0654 www.miratron.cc